

**Range: Traditional**

**Colour: Chapel Red**

**SKU: 350500010700000201150**

## Technical Data

|                                                            |         |
|------------------------------------------------------------|---------|
| Length (mm)                                                | 230     |
| Width (mm)                                                 | 110     |
| Height (mm)                                                | 76      |
| Dimensional Category                                       | DW1     |
| Average Weight / Unit (kg)                                 | 4       |
| Core Volume (%)                                            | 10      |
| Units per Square Metre                                     | 48.5    |
| Pack Size                                                  | 400     |
| Characteristic Unconfined Compressive Strength (f 'uc) MPa | >12     |
| Maximum Cold Water Absorption (%)                          | 10      |
| Initial Rate of Absorption (IRA) (kg/m2 min)               | 0.5-2.5 |

|                                          |                |
|------------------------------------------|----------------|
| Coefficient of Expansion e'Factor (mm/m) | 1.2            |
| Durability Class                         | Exposure Grade |
| Liability to Efflorescence               | Slight         |
| Lime Pitting Liability                   | Slight         |
| Solar Absorption                         | 0.73           |
| LRV                                      | 9.4            |
| Place of Manufacture                     | Victoria       |
| Product Warranty                         | 100 Years      |
| Solar Absorption                         | 0.73           |
| Meter squared                            | 48.5           |

Please note: FRL applies up to 3m high - restrained on top and bottom.