

Artisan NB Range Technical Data Sheet

BRICKWORKS

Product Range	Product Name	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Dimensional Category	Average Weight / Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f _{uc}) MPa	Maximum Cold Water Absorption (%)	Initial Rate of Absorption (IRA) (kg/m ² min)	Coefficient of Expansion Factor (mm/m)	Durability Class	Liability to Efflorescence	Lime Pitting Liability	LRV
Artisan NB	Aurora		TAS	230	110	76	DW1	4.15	<10	48.5	400	>15	<10	1.0-2.5	<1.2	Exposure Grade	Slight	Slight	29.2
Artisan NB	Avalanche		TAS	230	110	76	DW1	4.15	<10	48.5	400	>15	<10	1.0-2.5	<1.2	Exposure Grade	Slight	Slight	44.3
Artisan NB	Wolf		TAS	230	110	76	DW1	4.15	<10	48.5	400	>15	<10	1.0-2.5	<1.2	Exposure Grade	Slight	Slight	19.5
Artisan NB	Tundra		TAS	230	110	76	DW1	4.15	<10	48.5	400	>15	<10	1.0-2.5	<1.2	Exposure Grade	Slight	Slight	24.3

This Data represents average results from commercial production lots.
 If specific test results are required, sample should be taken from current production lots.
 AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.
 Please note: FRL applies up to 3m high - restrained on top and bottom.

NUBRİK